



# HiDM5 (All-Black)

## ALL-BLACK HIGH DENSITY MONO PERC MODULE

### 390 W ~ 405 W

#### CS1Y-390 | 395 | 400 | 405MS

Dimensions: 2021 × 996 × 35 mm (79.6 × 39.2 × 1.38 in)  
Weight: 22.6 kg (49.8 lbs)  
Max. System Voltage: 1000 V (IEC/UL)

#### MORE POWER



Aesthetically pleasing design blends into your roof



Maximize the light absorption area, module efficiency up to 20.1 %



Low temperature coefficient (Pmax): -0.37 % / °C



Better shading tolerance



enhanced product warranty on materials and workmanship\*



linear power output warranty\*

\*According to the applicable Canadian Solar Limited Warranty Statement.

#### MANAGEMENT SYSTEM CERTIFICATES\*

ISO 9001:2015 / Quality management system

ISO 14001:2015 / Standards for environmental management system

OHSAS 18001:2007 / International standards for occupational health & safety

#### MORE RELIABLE



Lower internal current, lower hot spot temperature



Minimizes micro-crack impacts



Heavy snow load up to 5400 Pa, wind load up to 2400 Pa\*

#### PRODUCT CERTIFICATES\*

As there are different certification requirements in different markets, please contact your local Canadian Solar sales representative for the specific certificates applicable to the products in the region in which the products are to be used.

**CANADIAN SOLAR INC.** is committed to providing high quality solar products, solar system solutions and services to customers around the world. No. 1 module supplier for quality and performance/price ratio in IHS Module Customer Insight Survey. As a leading PV project developer and manufacturer of solar modules with over 40 GW deployed around the world since 2001.

\* For detail information, please refer to Installation Manual.

#### CANADIAN SOLAR INC.

545 Speedvale Avenue West, Guelph, Ontario N1K 1E6, Canada, [www.canadiansolar.com](http://www.canadiansolar.com), [support@canadiansolar.com](mailto:support@canadiansolar.com)